



**Power-Light Emitting Diode 大功率发光二极管**

**Part NO.:P1WLRLXWL1 (产品型号)**



**Features:**

**Package Dimension:**

**Lens Color(胶体颜色) : Water Clear(透明)**

**Source Color(发光颜色) : Warm White(暖白色)**

**Bright BIN(亮度等级) : Ultra Bright(超高亮)**



**GaN/SiC**

**Absolute Maximum Ratings at Ta=25°C**

**Electrical Optical Characteristics at Ta=25°C**

Parameter	Symbol	Rating	Units
DC Forward Current	$I_F$	350	mA
Reverse Voltage	VR	5	V
LED junction Temperature ( at 350 mA )	$T_j$	125	°C
Operating Temperature	$T_{opr}$	-30 ~ +110	°C
Storage Temperature	$T_{stg}$	-40 ~ +120	°C
Manual Soldering Time at 260°C (MAX.)	$T_{sol}$	5	Seconds

Parameter	Symbol	condition	Min.	Typ.	Max.	Unit
Give out light the power	P	IF=350mA	---	1	---	W
Luminous Flux	Flux	IF=350mA	65	---	75	lm
Thermal Resistance Junction to Board	$R \theta_{J-B}$	IF=350mA	---	15	---	°C/W
Viewing Angle(发光角度)	$2 \theta_{1/2}$	IF=350mA	---	120		Deg
Color Temperature	TC	IF=350mA	3100	---	3200	K
Temperature Coefficient Of Forward Voltage	$\Delta V_F / \Delta T$	IF=350mA	---	-2	---	mV/°C
Forward Voltage	$V_F$	IF=350mA	3.5	---	3.7	V
Reverse Current	$I_R$	VR=-5V	---	---	100	μA